

In the claims:

Cancel claims 3 and 5 without prejudice.

1. (Currently amended) A unit for quick connecting conductors to terminals, comprising a single body in which two conductors are introducible; at least two mechanical devices each formed and operative for a quick connection of one conductor to each terminal and for disconnection of said one conductor from each terminal, said mechanical devices being formed so that each of said mechanical devices provides a quick connection of one of the conductors to each of the terminal in said single body, and a disconnection of said one conductor from each terminal in said single body without impairing another of the mechanical devices and thereby another conductor, so that the two conductors can be connected or disconnected individually and separately from one another , each of said mechanical devices including an operating lever having two identical and independent levers symmetrically located with respect to a contact plane, each lever being provided with a top flat base for operation and ending in a rounded lower end, a stop latch provided at said rounded lower end and preventing an unwanted exit of said lever from a place where said lever is located, a resilient metal strip situated under said lever and keeping said lever raised,

said resilient metal strip having a top end divided into two symmetrical and spaced parts including one part for each lever, said ends being formed so as to pass under ends of the conductors to be connected, side holes arranged so that the conductors to be connected are introducible from outside through said holes.

2. (Previously amended) A unit as defined in claim 1, wherein said body is provided with means for locating said body in an electrical device, said body having internal walls which delimit areas for locating said mechanical devices.

Claim 3 cancelled.

4. (currently amended) A unit as defined in claim 31; and further comprising a bottom, said metal strip being supported on said bottom.

Claim 5 cancelled.

6. (Currently amended) A unit as defined in claim 31; and further comprising an elastic metal band having two top divided parts under

said levers and arranged symmetrically and independently; and two contacting bases which are formed also symmetrically and independently.

7. (New) A unit for quick connecting conductors to terminals, comprising a single body in which two conductors are introducible; at least two mechanical devices each formed and operative for a quick connection of one conductor to each terminal and for disconnection of said one conductor from each terminal, said mechanical devices being formed so that each of said mechanical devices provides a quick connection of one of the conductors to each of the terminal in said single body, and a disconnection of said one conductor from each terminal in said single body without impairing another of the mechanical devices and thereby another conductor, so that the two conductors can be connected or disconnected individually and separately from one another, each of said mechanical devices including an operating lever having two identical and independent levers symmetrically located with respect to a contact plane, each lever being provided with a top flat base for operation and ending in a rounded lower end, a stop latch provided at said rounded lower end and preventing an unwanted exit of said lever from a place where said lever is located, a resilient metal strip situated under said lever and keeping said lever raised, said resilient metal strip having a top end divided into two symmetrical and spaced parts including

one part for each lever, said ends being formed so as to pass under ends of the conductors to be connected, side holes arranged so that the conductors to be connected are introducible from outside through said holes, said levers being arranged so that when a corresponding one of said levers is pushed said corresponding lever goes down against an action of said resilient metal strip, which goes down against an action of said resilient metal strip, which goes down allowing an easy and immediate introduction of an end of the conductor to be connected through said side hole and when said lever is no longer pressed down said lever is going back to an initial position under the action of said elastic metal strip which in turn presses and locks the conductor to connect said conductor.